

MP-AMP30

Media Presentation Audio Amplifier

The Crestron® MP-AMP30 provides a convenient, low-cost audio amplifier solution for a variety of applications. A perfect complement to the entire Media Presentation line from Crestron, it features a compact surface-mountable design that installs virtually anywhere without requiring an equipment rack. High-efficiency Class D circuitry delivers 15 Watts per channel to drive one or two pairs of 8 Ohm speakers, or a single pair of 4 Ohm speakers, making it ideal to support stereo speakers at the front of a room or mono speakers in the ceiling. Mono-summed operation is enabled by changing two jumpers on the front panel.

Refined, reliable operation is ensured thanks to pop-free turn-on circuitry and electronic short-circuit and overload protection. An energy-saving design achieves optimum efficiency under load, and also powers down automatically when no input signal is detected for more than 5 minutes, reducing overall power consumption and heat as part of a green system design. Its extruded aluminum housing is both attractive and effective at dissipating heat, affording a silent running design without cooling fans.

Installation and setup of the MP-AMP30 is simple. Detachable output connectors facilitate the termination of speaker wiring up to 16 gauge. RCA inputs connect directly to the line output of a video projector or display, audio processor, mixer, or AV switcher. Rotary controls provide for adjusting the overall speaker volume, as well as bass and treble. For quiet environments, loudness compensation is employed by setting the volume control below the center detent position.

> *Compact surface mount power amplifier*

> *15 Watts per channel into 8 or 4 Ohms*

> *Stereo or mono-summed operation*

> *High-efficiency Class D topology*

> *Energy saving design reduces power consumption when idle*

> *Convection cooled for noiseless operation*

> *Simple volume, bass, and treble adjustments*

> *Built-in loudness contour circuit*

> *Electronic short-circuit and overload protection*

> *Detachable terminal block speaker connections*

> *Unbalanced RCA line inputs, 3' cable included*

SPECIFICATIONS

Audio

Input Volume Range: -55dB to +20dB

Loudness: Active at volume settings below center detent

Bass Gain Range: ±15dB @ 100Hz

Treble Gain Range: ±15dB @ 10kHz

Frequency Response: 20Hz to 20kHz ±0.5dB



S/N Ratio: 75dB 20Hz to 20kHz A-weighted

THD+N: 0.7% 20Hz to 20kHz

Output Power: 15 Watts per channel at 8 or 4 Ohms

Connectors - Top Panel

AUDIO OUT 8?: (2) 2-pin 3.5mm detachable terminal blocks;

Left & right channel speaker-level audio outputs;

Wire Size: Connector accepts 16 AWG maximum;

Output Power: 15 Watts per channel at 8 or 4 Ohms

Connectors - Bottom Panel

AUDIO IN: (2) RCA female, unbalanced stereo line-level audio input;

Maximum Input Level: 2 Vrms;

Input Impedance: 18k Ohms;

3 ft (0.9 m) stereo RCA-RCA cable included

PWR 24VDC 2.0A: (1) 2.1mm barrel DC power jack;

24 Volt DC power input;

(power supply included)

Controls & Indicators

BASS: Rotary low frequency boost/cut adjustment, flat at center detent

TREBLE: Rotary high frequency boost/cut adjustment, flat at center detent

VOL: Rotary input level adjustment

ST, MO: Mode selection jumpers, select stereo or mono-summed operation

Power: (1) green LED, indicates operating power supplied from external power supply

Power Requirements

Power Consumption: 2 Amps @ 24 Volts DC (power supply included)

Environmental

Temperature: 41° to 104°F (5° to 40°C)

Humidity: 10% to 90% RH (non-condensing)

Heat Dissipation: 21 BTU/Hr

Enclosure

Chassis: Aluminum w/polycarbonate label overlay and (4) integral mounting flanges

Mounting: Freestanding or surface mount

MP-AMP30 Media Presentation Audio Amplifier

Dimensions

Height: 5.85 in (149 mm)

Width: 3.91 in (100 mm)

Depth: 1.43 in (37 mm)

Weight

11.8 oz (335 g)

Available Models

MP-AMP30: Media Presentation Audio Amplifier

Available Accessories

CBL-RCA2-1.5: Crestron® Certified RCA Stereo Audio Interface Cable, 1.5 ft

CBL-RCA2-3: Crestron® Certified RCA Stereo Audio Interface Cable, 3 ft

CBL-RCA2-6: Crestron® Certified RCA Stereo Audio Interface Cable, 6 ft

CBL-RCA2-12: Crestron® Certified RCA Stereo Audio Interface Cable, 12 ft

MP-WP100-B: Media Presentation Wall Plate - RCA Composite Video w/RCA Stereo Audio, Black

MP-WP100-W: Media Presentation Wall Plate - RCA Composite Video w/RCA Stereo Audio, White

MP-WP110-B: Media Presentation Wall Plate - Mini-DIN S-Video w/RCA Stereo Audio, Black

MP-WP110-W: Media Presentation Wall Plate - Mini-DIN S-Video w/RCA Stereo Audio, White

MP-WP120-B: Media Presentation Wall Plate - RCA Component Video w/RCA Stereo Audio, Black

MP-WP120-W: Media Presentation Wall Plate - RCA Component Video w/RCA Stereo Audio, White

MP-WP125-B: Media Presentation Wall Plate - RCA Component & Composite Video w/2x RCA Stereo Audio, Black

MP-WP125-W: Media Presentation Wall Plate - RCA Component & Composite Video w/2x RCA Stereo Audio, White

MP-WP130-B: Media Presentation Wall Plate - DB15HD Computer VGA w/Mini-TRS Stereo Audio, Bulkhead, Black

MP-WP130-W: Media Presentation Wall Plate - DB15HD Computer VGA w/Mini-TRS Stereo Audio, Bulkhead, White

MP-WP131-B: Media Presentation Wall Plate - DB15HD Computer VGA w/Mini-TRS Stereo Audio, Breakout, Black

MP-WP131-W: Media Presentation Wall Plate - DB15HD Computer VGA w/Mini-TRS Stereo Audio, Breakout, White

MP-WP140-B: Media Presentation Wall Plate - DVI-I w/Mini-TRS Stereo Audio, Black

MP-WP140-W: Media Presentation Wall Plate - DVI-I w/Mini-TRS Stereo Audio, White

MP-WP150-B: Media Presentation Wall Plate - HDMI™ w/Mini-TRS Stereo Audio, Black

MP-WP150-W: Media Presentation Wall Plate - HDMI™ w/Mini-TRS Stereo Audio, White

MP-WP160-B: Media Presentation Wall Plate - DisplayPort w/Mini-TRS Stereo Audio, Black

MP-WP160-W: Media Presentation Wall Plate - DisplayPort w/Mini-TRS Stereo Audio, White



MP-AMP30 Media Presentation Audio Amplifier

