

Y-BUS CONTROL CARDS

C2COM-2 RS-232/422/485 Interface for Y-Bus Expansion Slot

The C2COM-2 installs in any Y-Bus expansion slot of a 2-Series control system to provide two bi-directional RS-232/422/485 ports with hardware handshaking.

SPECIFICATIONS

Connectors

COM A - B: (2) DB9 male
(2) Bidirectional RS-232/422/485 ports
Up to 115.2K baud
Hardware and software handshaking support

Power Requirements

2 Watts (0.083 Amps @ 24 Volts DC)

AVAILABLE ACCESSORIES

- ▶ CNSP-XX
Custom Serial Interface Cable



C2COM-3 RS-232/422/485 Interface for Y-Bus Expansion Slot

The C2COM-3 installs in any Y-Bus expansion slot of a 2-Series control system to provide three bi-directional RS-232/422/485 ports with hardware handshaking.

SPECIFICATIONS

Connectors

COM A - C: (3) DB9 male
(3) Bidirectional RS-232/422/485 ports
Up to 115.2K baud
Hardware and software handshaking support

Power Requirements

2 Watts (0.083 Amps @ 24 Volts DC)

AVAILABLE ACCESSORIES

- ▶ CNSP-XX
Custom Serial Interface Cable

