

### Y-BUS CONTROL CARDS

#### CNXRY-16 16 Relay Card for Y-Bus Expansion Slot

The CNXRY-16 installs in any Y-Bus expansion slot of a 2-Series control system to provide 16 isolated, low-voltage relay closures. Each group of eight relays is referenced to a shared, floating common.

#### SPECIFICATIONS

##### Connectors

**RELAY OUTPUT A1 – A8, B1 – B8:** (2) 9-pin 5mm detachable terminal blocks  
(2 x 8) Normally open, isolated relays (each group of 8 referenced to shared common)  
Rated 1A, 30V AC/DC  
MOV arc suppression across contacts

##### Power Requirements

5 Watts (0.208 Amp @ 24 Volts DC)



#### CNXMIDI MIDI Interface Card for Y-Bus Expansion Slot

The CNXMIDI is a fully programmable MIDI in, out and thru interface. It installs in any Y-Bus expansion slot of a 2-Series control system.

#### SPECIFICATIONS

##### Connectors

**MIDI IN:** (1) 5-pin DIN female  
**MIDI OUT:** (1) 5-pin DIN female  
**MIDI THRU:** (1) 5-pin DIN female

##### Power Requirements

4 Watts (0.167 Amp @ 24 Volts DC)

